


DOUBLE-GLASS BIFACIAL N-TYPE 495~505 Watt



TOPCon



Cutting Free Technology
Minimized micro-crack



Bifacial Mono Module
Capable of generating power at back side, at least 80% efficiency of the front side



Anti-PID(potential induced degradation)
Passed anti-PID test under 85°C damp heat 85% relative humidity for 192 hours



Lower LCOE
Lower shading and resistive loss
Lower temperature coefficient



Outstanding mechanical load resistance
2400 Pa wind load, 5400 Pa snow load



15 15-year product warranty
30 30-year linear power output



CEC Listed



IEC 61215, IEC 61730
ISO 9001: 2015 (Quality management systems)
ISO 14001: 2015 (Environmental management systems)
ISO 45001: 2018 (Occupational health and safety)
UNI 9177 la CLASSE DI REAZIONE AL FUOCO:1



Add: No. 238 Yunlin Middle Road, Wangchun Industrial District, Ningbo China

Tel: +86-574-28828939 Email: sales@ulsolar.com.cn

Fax: +86-574-28828997 Web: www.ulicasolar.com

TOPCon(N TYPE)495~505Watt

ELECTRICAL SPECIFICATIONS

Module Type		UL-495M-120BDGN		UL-500M-120BDGN		UL-505M-120BDGN	
		STC*	NOCT*	STC*	NOCT*	STC*	NOCT*
Maximum Power (Pmax)	W	495	375	500	379	505	383
Maximum Power Voltage (Vmp)V		36.85	33.90	37.02	34.06	37.18	34.21
Maximum Power Current (Imp) A		13.43	11.06	13.51	11.13	13.58	11.19
Open-circuit Voltage (Voc)	V	43.52	39.60	43.78	39.84	43.98	40.02
Short-circuit Current (Isc)	A	14.43	11.64	14.48	11.68	14.54	11.73
Module Efficiency STC	%	22.36		22.59		22.81	
Operating Temperature				-40°C~85°C			
Maximum system voltage				DC1500V(IEC)			
Maximum series fuse rating				30A			
Power tolerance				0~+5Watt			
Temperature coefficients of Pmax				-0.29%/°C			
Temperature coefficients of Voc				-0.25%/°C			
Temperature coefficients of Isc				0.046%/°C			
Nominal operating cell temperature (NOCT)				43±2°C			

*STC : Cell temperature: 25°C, Irradiance: 1000 W/m², Air mass: 1.5G

*NOCT : Air temperature: 20°C, Irradiance: 800 W/m², Air mass: 1.5G, Wind speed: 1 m/s

SPECIFICATIONS



Cell Type	N type Mono-crystalline		
No. of cells	120(6×10×2)		
Dimensions	1952*1134*30mm		
Weight	26.5kg		
Glass	2.0mm+2.0mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass		
Junction Box	IP68, 3 diodes		
Connector	MC4 Compatible		
Cable Length (Including Connector)	Landscape: (+)1200mm/(-)1200mm or Customized Length		
Packaging Configuration	Two Box=One Pallet 36pcs/Box, 72pcs/Pallet, 864pcs/40HQ Container		

Electrical characteristics with different rear side power gain(reference to 500 W front)



Pmax/W	Voc/V	Isc/A	Vmp/V	Imp/A	Pmax gain
500	43.78	14.48	37.02	13.51	0%
525	43.78	15.20	37.02	14.18	5%
550	43.78	15.93	37.02	14.86	10%
575	43.78	16.65	37.02	15.53	15%
600	43.78	17.38	37.02	16.21	20%
625	43.78	18.10	37.02	16.88	25%
650	43.78	18.82	37.02	17.56	30%

I-V CURVE

I-V characteristics at different irradiances (reference to 500 W)



I-V characteristics at different temperature



Specifications included in this datasheet are subject to change without notice.

Ulica Solar reserves the right of final interpretation.

Version No.: UL-1952-120BDGNBBC-30-EN-V1.1